

Description

Self-aligning collar, 303 stainless steel - tension application - cadmium plated, HL75 Series

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL758A
Minimum Qty (MOQ):	10
NSN:	5320-00-135-3070
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N HL75-8A Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.465 Inches Minimum And 0.475 Inches Maximum
<b>Collar Overall Height:</b>	0.522 Inches Minimum And 0.552 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.333 Inches Nominal
<b>End Item Identification:</b>	W/s: Aircraft, Galaxy C-5; Aircraft, Stratofortress B-52; Aircraft, Stratolifter C-135; Aircraft, Hx Unique
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL75-8A](https://military-fasteners.com/collars/pin_rivet+collars/HL75-8A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.