

Description

Thread Size: 1/8", with washer, HL77 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL775DADW
Minimum Qty (MOQ):	5
NSN:	5320-01-284-0879
Schedule B:	7616.99.5090
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL77-5DADW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Collar Inside Diameter:	0.166 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Washer Finish Is Solid Film Lube Per Mil-I-8937; Heat Treat,t6 Cond Per Mil-h-6088 Washer For Matl 2024 Only
Heat Treatment:	T-6 Solution Heat Treated Collar
Heat Treatment:	T-6 Solution Heat Treated Washer
Material:	Aluminum Alloy 2024 Washer Or Aluminum Alloy 5052 Washer
Material:	Aluminum Alloy 2024 Body
Material Document And Classification:	Qq-a-250/4 Fed Spec 1st Material Response Washer Or Qq-a-250/5 Fed Spec 1st Material Response Washer Or Qq-a-250/8 Fed Spec 2nd Material Response Washer
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Collar Or Qq-a-225/6 Fed Spec Single Material Response Collar
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL77-5DADW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.