

Description

Thread Size: 1/4", HL78 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL7810
Minimum Qty (MOQ):	1
NSN:	5320-01-194-0735
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL78-10 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.512 Inches Minimum And 0.518 Inches Maximum
<b>Collar Overall Height:</b>	0.652 Inches Minimum And 0.672 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.330 Inches Minimum And 0.336 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL78-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.