

**Description**

tension application, high temperature steel alloy, silver plated, HL78 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL785
Minimum Qty (MOQ):	5
NSN:	5320-01-527-0716
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N HL78-5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.283 Inches Minimum And 0.287 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.166 Inches Minimum And 0.173 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.125 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	5731 Assn Std All Material Responses Overall Or 5734 Assn Std All Material Responses Overall Or 5736 Assn Std All Material Responses Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	2410 Assn Std All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rievet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rievet+collars/HL78-5](https://military-fasteners.com/collars/pin_rievet+collars/HL78-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.