

Description

tension application, high temperature steel alloy, silver plated, HL78 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL785
Minimum Qty (MOQ):	5
NSN:	5320-01-527-0716
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL78-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.283 Inches Minimum And 0.287 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.166 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.125 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Overall
Material Document And Classification:	5731 Assn Std All Material Responses Overall Or 5734 Assn Std All Material Responses Overall Or 5736 Assn Std All Material Responses Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	2410 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL78-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.