

Description

tension application, high temperature steel alloy, silver plated, break off type, HL78 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL786 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-073-1472 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N HL78-6 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.303 Inches Minimum And 0.307 Inches Maximum |
| Collar Overall Height: | 0.437 Inches Minimum And 0.457 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.195 Inches Minimum And 0.200 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Iron Alloy 660 Overall |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL78-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.