

Description

HL78 series collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL78DU8
Minimum Qty (MOQ):	5
NSN:	5320-01-615-2347
Schedule B:	7318.15.8085
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N HL78DU8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.532 Inches Minimum And 0.552 Inches Maximum
Lubrication:	Solid Film
Collar Inside Diameter:	0.268 Inches Minimum And 0.272 Inches Maximum
End Item Identification:	C-5 Aircraft
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL78DU8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.