

## Description

shear application, aluminum alloy, brown anodized, HL79 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[BACC30M10](#)

SKU / Model:

HL7910

Minimum Qty (MOQ):

20

NSN:

5320-00-968-9211

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N HL79-10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.532 Inches Minimum And 0.538 Inches Maximum
Collar Overall Height:	0.652 Inches Minimum And 0.672 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.330 Inches Minimum And 0.336 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Red
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL79-10](https://military-fasteners.com/collars/pin_rivet+collars/HL79-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.