

Description

shear application, aluminum alloy, brown anodized, HL79 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[BACC30M10](#)

SKU / Model:

HL7910

Minimum Qty (MOQ):

20

NSN:

5320-00-968-9211

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL79-10 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Identification Code Color: | Red |
| Collar Outside Diameter: | 0.532 Inches Minimum And 0.538 Inches Maximum |
| Collar Overall Height: | 0.652 Inches Minimum And 0.672 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.330 Inches Minimum And 0.336 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | Color Red |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL79-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.