

Description

red anodized, aluminum alloy, break off style, HL79 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL7912
Minimum Qty (MOQ):	10
NSN:	5320-00-867-8707
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL79-12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.642 Inches Minimum And 0.649 Inches Maximum
Collar Overall Height:	0.724 Inches Minimum And 0.744 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.392 Inches Minimum And 0.398 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Red
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL79-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.