

**Description**

shear application, 2024-t6 aluminum alloy, brown anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[BACC30M8](#)

SKU / Model:	HL798
Minimum Qty (MOQ):	10
NSN:	5320-00-968-9210
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL79-8 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Red
<b>Collar Outside Diameter:</b>	0.418 Inches Minimum And 0.422 Inches Maximum
<b>Collar Overall Height:</b>	0.532 Inches Minimum And 0.552 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.268 Inches Minimum And 0.272 Inches Maximum
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Special Features:</b>	Color Red
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-riquet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_riquet+collars/HL79-8](https://military-fasteners.com/collars/pin_riquet+collars/HL79-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.