

## **P/N HL82-10A**

## **Description**

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL8210A

Minimum Qty (MOQ): 5 EA

NSN: 5320-00-414-7698

Schedule B: 7616.10.1000

ECCN: 9A991

National Motor Freight: 013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# **P/N HL82-10A Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.610 Inches Minimum And 0.620 Inches Maximum
Collar Overall Height:	0.690 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.333 Inches Nominal
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this hl collar/washer assembly from our inventory online by visiting <a href="https://military-fasteners.com/collars/HL82-10A">https://military-fasteners.com/collars/HL82-10A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/HL82-10A">https://military-fasteners.com/collars/HL82-10A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/HL82-10A">https://military-fasteners.com/collars/HL82-10A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/HL82-10A">https://military-fasteners.com/collars/HL82-10A</a> and selecting the quantity you want <a href="https://military-fasteners.com/collars/HL82-10A">https://military-fasteners.com/collars/HL82-10A</a> and selecting the property of the propert