

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL8210ADW
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-187-9576
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL82-10ADW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.610 Inches Minimum And 0.620 Inches Maximum
Collar Overall Height:	0.690 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.333 Inches Nominal
Features Provided:	Washer
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Washer Material 17-7ph And 15-7mo Heat Treat To Th1050 Per Mil-h-6875; Washer Has Solid Film Lube
Heat Treatment:	H-1025 Strain Hardened Washer
Heat Treatment:	T-6 Solution Heat Treated Collar
Material:	Aluminum Alloy 2024 Body
Material:	Steel Comp 630 Washer Or Steel Comp 631 Washer Or Steel Comp 632 Washer
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Washer Or Ams 5528 Assn Std 2nd Material Response Washer Or Ams 5520 Assn Std 3rd Material Response Washer
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Collar Or Qq-a-225/6 Fed Spec Single Material Response Collar
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Thread Series Designator:	Unjf

How to Order

Order this hl collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL82-10ADW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.