

Description

Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL8212AW
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-151-5518
Schedule B:	7318.22.0000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N HL82-12AW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.675 Inches Minimum And 0.685 Inches Maximum
Collar Overall Height:	0.720 Inches Minimum And 0.740 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.395 Inches Nominal
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this hl collar/washer assembly from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL82-12AW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.