

Description

Thread Size: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | HL825ADW |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-176-2030 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL82-5ADW Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Identification Code Color: | Red |
| Collar Outside Diameter: | 0.355 Inches Minimum And 0.365 Inches Maximum |
| Collar Overall Height: | 0.445 Inches Nominal |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.235 Inches Nominal |
| Features Provided: | Washer |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Collar Style: | Threaded (break Off) Type |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Assn Std Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this hl washer from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL82-5ADW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.