

## **P/N HL82-5ADW**

### **Description**

Thread Size: 1/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model:	HL825ADW
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-176-2030
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

## **P/N HL82-5ADW Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.355 Inches Minimum And 0.365 Inches Maximum
Collar Overall Height:	0.445 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.235 Inches Nominal
Features Provided:	Washer
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Assn Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

### **How to Order**

Order this hl washer from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/HL82-5ADW">https://military-fasteners.com/collars/pin\_rivet+collars/HL82-5ADW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.