

Description

self-aligning collar assembly shear application - assembly of hl82-#a collar and hl85-#pbw washer (cad ii plated washer)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL825APBW
Minimum Qty (MOQ):	10
NSN:	5320-01-106-6749
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL82-5APBW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.355 Inches Minimum And 0.365 Inches Maximum
Collar Overall Height:	0.445 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.184 Inches Nominal
Features Provided:	Washer
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Red
Heat Treatment:	T-6 Solution Heat Treated Collar
Material:	Aluminum Alloy 2024 Body
Material:	Steel Comp 630 Washer Or Steel Comp 631 Washer Or Steel Comp 632 Washer
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Washer Or Ams 5528 Assn Std 2nd Material Response Washer Or Ams 5520 Assn Std 3rd Material Response Washer
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Collar
Surface Treatment:	Cadmium Washer And Chromate Washer
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Washer
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL82-5APBW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.