

**Description**

self-aligning collar shear application, aluminum, red anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL826A
Minimum Qty (MOQ):	25
NSN:	5320-00-959-0134
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N HL82-6A Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Red
<b>Collar Outside Diameter:</b>	0.355 Inches Minimum And 0.365 Inches Maximum
<b>Collar Overall Height:</b>	0.445 Inches Nominal
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.210 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-riev collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL82-6A](https://military-fasteners.com/collars/pin_rivet+collars/HL82-6A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.