

## Description


self-aligning collar assembly shear application - assembly of hl82-#a collar and hl85-#w washer (cad i plated washer)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL826AW
Minimum Qty (MOQ):	10
NSN:	5320-00-225-0496
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N HL82-6AW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Overall Height:	0.400 Inches Minimum And 0.420 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Collar With Washer
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL82-6AW](https://military-fasteners.com/collars/pin_rivet+collars/HL82-6AW) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.