

Description

self-aligning collar shear application - aluminum - red anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL828A
Minimum Qty (MOQ):	10
NSN:	5320-00-959-0126
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N HL82-8A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Collar Overall Height:	0.570 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.270 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL82-8A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.