

## Description


self-aligning, collar assembly, shear application, assembly of HL82 collar and HL85 washer, CAD II plated washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL828APBW
Minimum Qty (MOQ):	10
NSN:	5320-01-019-6567
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N HL82-8APBW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Red
Collar Outside Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Collar Overall Height:	0.520 Inches Minimum And 0.540 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.270 Inches Nominal
Features Provided:	Washer
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Collar Color Red
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL82-8APBW](https://military-fasteners.com/collars/pin_rivet+collars/HL82-8APBW) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.