

Description


self-aligning, collar assembly, shear application, assembly of HL82 collar and HL85 washer, CAD II plated washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | HL828APBW |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-019-6567 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N HL82-8APBW Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Identification Code Color: | Red |
| Collar Outside Diameter: | 0.465 Inches Minimum And 0.475 Inches Maximum |
| Collar Overall Height: | 0.520 Inches Minimum And 0.540 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.270 Inches Nominal |
| Features Provided: | Washer |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | Collar Color Red |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL82-8APBW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.