

P/N HL82-8AW

Military-Fasteners.com

Description

Thread Size: 1/4", with washer, self-aligning collar assembly, HL82 series collar

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

| SKU / Model: | HL828AW |
|-------------------------|---------------------|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-917-4810 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N HL82-8AW Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.465 Inches Minimum And 0.475 Inches Maximum |
| Collar Overall Height: | 0.570 Inches Nominal |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.270 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | Washer Included |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this collar from our inventory online by visiting <u>https://military-fasteners.com/collars/collars/HL82-8AW</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.