

Description

HL86-12 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL8612
Minimum Qty (MOQ):	5
NSN:	5320-01-005-2349
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL86-12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.622 Inches Minimum And 0.628 Inches Maximum
Collar Overall Height:	0.724 Inches Minimum And 0.744 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.376 Inches Minimum And 0.388 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL86-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.