

Description

HL86-12 Pin-Rivet Collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL8612
Minimum Qty (MOQ):	5
NSN:	5320-01-005-2349
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N HL86-12 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.622 Inches Minimum And 0.628 Inches Maximum
<b>Collar Overall Height:</b>	0.724 Inches Minimum And 0.744 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.376 Inches Minimum And 0.388 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL86-12](https://military-fasteners.com/collars/pin_rivet+collars/HL86-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.