

Description

Thread: 1/4-28, tension application, fine thread, 303 stainless steel, cadmium plated, Hi-Lok, HL86 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL868
Minimum Qty (MOQ):	5
NSN:	5320-00-145-5923
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL86-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.532 Inches Minimum And 0.552 Inches Maximum
Lubrication:	Grease Film
Collar Inside Diameter:	0.252 Inches Minimum And 0.261 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL86-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.