

Description

Thread Size: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[HL86KP-10](#)

SKU / Model:	HL86KP10
Minimum Qty (MOQ):	1
NSN:	5320-01-453-9978
Schedule B:	7326.90.8588
ECCN:	EAR99



P/N HL86KP10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.512 Inches Minimum And 0.518 Inches Maximum
Collar Overall Height:	0.652 Inches Minimum And 0.672 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.314 Inches Minimum And 0.325 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.3125 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Violet To Purple;1/16 Inch Grip Variation Tension Application
Material:	Steel Comp 303se Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416.ty2.cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL86KP10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.