

Description

Thread Size: 1/4", HL86 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[HL86PB-6](#)

| | |
|-------------------------|---|
| SKU / Model: | HL86PB6 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-948-4213 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL86PB6 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.303 Inches Minimum And 0.307 Inches Maximum |
| Collar Overall Height: | 0.437 Inches Minimum And 0.457 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.192 Inches Minimum And 0.200 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp 303se Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL86PB6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.