

Description

Thread Size: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL86PB8
Minimum Qty (MOQ):	5
NSN:	5320-00-950-3022
Schedule B:	7326.90.8588
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL86PB8 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.408 Inches Minimum And 0.412 Inches Maximum
<b>Collar Overall Height:</b>	0.532 Inches Minimum And 0.552 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.252 Inches Minimum And 0.261 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL86PB8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.