

**Description**

Thread Size: 1/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL86PBW5
Minimum Qty (MOQ):	10
NSN:	5320-00-869-1496
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL86PBW5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.283 Inches Minimum And 0.287 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Lubrication:</b>	Grease Film Or Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.166 Inches Minimum And 0.173 Inches Maximum
<b>Features Provided:</b>	Washer
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL86PBW5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.