

Description

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL86PBW8
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-869-1494
Schedule B:	7318.22.0000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N HL86PBW8 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.408 Inches Minimum And 0.412 Inches Maximum
<b>Collar Overall Height:</b>	0.532 Inches Minimum And 0.552 Inches Maximum
<b>Lubrication:</b>	Grease Film Or Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.252 Inches Minimum And 0.261 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hl collar/washer assembly from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL86PBW8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.