

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL86TW8
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-234-7893
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL86TW8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Blue
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.532 Inches Minimum And 0.552 Inches Maximum
Lubrication:	Grease Film Or Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.252 Inches Minimum And 0.256 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Washer Color Blue
Material:	Aluminum Alloy 2024 Washer
Material:	Steel Comp 303se Body
Surface Treatment:	Anodize Washer
Surface Treatment:	Cadmium Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Washer
Surface Treatment Document And Classification:	Qq-p-416, Type 1, Class 2 Fed Spec Single Treatment Response Body
Thread Series Designator:	Unjf

How to Order

Order this hl collar/washer assembly from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL86TW8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.