

Description

Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL8714
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-416-1863
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N HL87-14 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.727 Inches Minimum And 0.733 Inches Maximum
<b>Collar Overall Height:</b>	0.842 Inches Minimum And 0.862 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.457 Inches Minimum And 0.463 Inches Maximum
<b>Nominal Thread Size:</b>	0.438 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Qq-s-764 Fed Spec Single Material Response Overall Or Ams5640 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	73197-hl87 Manufacturers Standard

## How to Order

Order this hl collar from our inventory online by visiting <https://military-fasteners.com/collars/collars/HL87-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.