

Description

tension application, oversized, 303 stainless steel, cadmium plated, HL87 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL878
Minimum Qty (MOQ):	5
NSN:	5320-00-935-9053
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL87-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.532 Inches Minimum And 0.552 Inches Maximum
Lubrication:	Grease Film
Collar Inside Diameter:	0.268 Inches Minimum And 0.272 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL87-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.