

Description

HL90 series collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL90LP10A
Minimum Qty (MOQ):	10
NSN:	5320-01-044-7543
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N HL90LP10A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Natural
Collar Outside Diameter:	0.512 Inches Minimum And 0.518 Inches Maximum
Collar Overall Height:	0.682 Inches Minimum And 0.702 Inches Maximum
Lubrication:	Solid Film
Collar Inside Diameter:	0.314 Inches Minimum And 0.325 Inches Maximum
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riev collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL90LP10A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.