

Description

shear application - 2024-t6 aluminum alloy - anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL90LP5A
Minimum Qty (MOQ):	10
NSN:	5320-01-005-3241
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N HL90LP5A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Natural
Collar Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Collar Overall Height:	0.457 Inches Minimum And 0.477 Inches Maximum
Collar Inside Diameter:	0.166 Inches Minimum And 0.173 Inches Maximum
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL90LP5A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.