

## Description

HL93 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL9312
Minimum Qty (MOQ):	5
NSN:	5320-01-216-0351
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

# P/N HL93-12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.677 Inches Minimum And 0.683 Inches Maximum
Collar Overall Height:	0.724 Inches Minimum And 0.744 Inches Maximum
Collar Inside Diameter:	0.410 Inches Minimum And 0.416 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL93-12](https://military-fasteners.com/collars/pin_rivet+collars/HL93-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.