

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL9314
Minimum Qty (MOQ):	1
NSN:	5320-01-416-1864
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL93-14 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.742 Inches Minimum And 0.748 Inches Maximum
Collar Overall Height:	0.855 Inches Minimum And 0.875 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.475 Inches Minimum And 0.481 Inches Maximum
Nominal Thread Size:	0.438 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	For Use On 1/32" Oversize Hi-lok Pins.
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall Or Ams5640 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl93 Manufacturers Standard

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL93-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.