

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL9314 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5320-01-416-1864 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N HL93-14 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.742 Inches Minimum And 0.748 Inches Maximum |
| Collar Overall Height: | 0.855 Inches Minimum And 0.875 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.475 Inches Minimum And 0.481 Inches Maximum |
| Nominal Thread Size: | 0.438 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | For Use On 1/32" Oversize Hi-lok Pins. |
| Material: | Steel Comp 303se Overall |
| Material Document And Classification: | Qq-s-764 Fed Spec Single Material Response Overall Or Ams5640 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 73197-hl93 Manufacturers Standard |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL93-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.