

Description

HL93 series collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL9316
Minimum Qty (MOQ):	1
NSN:	5320-01-194-7104
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL93-16 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.870 Inches Minimum And 0.880 Inches Maximum
Collar Overall Height:	0.922 Inches Minimum And 0.942 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.537 Inches Minimum And 0.543 Inches Maximum
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL93-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.