

**Description**

HL93 series collar

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL9316
Minimum Qty (MOQ):	1
NSN:	5320-01-194-7104
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL93-16 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.870 Inches Minimum And 0.880 Inches Maximum
<b>Collar Overall Height:</b>	0.922 Inches Minimum And 0.942 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.537 Inches Minimum And 0.543 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.500 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL93-16](https://military-fasteners.com/collars/pin_rivet+collars/HL93-16) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.