

Description

tension application, oversized, stainless steel, cadmium plated, HL93 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL936
Minimum Qty (MOQ):	10
NSN:	5320-01-051-3485
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL93-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Collar Overall Height:	0.437 Inches Minimum And 0.457 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.223 Inches Minimum And 0.227 Inches Maximum
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall
Material Document And Classification:	Ams 5640 Assn Std 1st Material Response Overall Or Ams 5640 Assn Std 2nd Material Response Overall Or Qq-s-764 Fed Spec 2nd Material Response Overall Or Ams 5640 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL93-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.