

**Description**

tension application, oversized 303 stainless steel, cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL9410
Minimum Qty (MOQ):	2
NSN:	5320-00-438-9470
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron

NO IMAGE  
AVAILABLE

## P/N HL94-10 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.532 Inches Minimum And 0.538 Inches Maximum
<b>Collar Overall Height:</b>	0.652 Inches Minimum And 0.672 Inches Maximum
<b>Collar Inside Diameter:</b>	0.330 Inches Minimum And 0.336 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.3125 Inches
<b>Criticality Code Justification:</b>	Cqjx
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4971 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-riquet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL94-10](https://military-fasteners.com/collars/pin_rivet+collars/HL94-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.