

**Description**

HL94 series collar

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL9412
Minimum Qty (MOQ):	5
NSN:	5320-00-438-9468
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL94-12 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.642 Inches Minimum And 0.649 Inches Maximum
<b>Collar Overall Height:</b>	0.724 Inches Minimum And 0.744 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.392 Inches Minimum And 0.398 Inches Maximum
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4971 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL94-12](https://military-fasteners.com/collars/pin_rivet+collars/HL94-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.