

Description

Collar, tension application, oversized 303 stainless steel, cadmium plated, Hi-Lok, HL94 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL945
Minimum Qty (MOQ):	10
NSN:	5320-00-136-2915
Schedule B:	7318.19.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL94-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Collar Inside Diameter:	0.166 Inches Minimum And 0.170 Inches Maximum
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL94-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.