

Description

Collar, tension application, oversized 303 stainless steel, cadmium plated, Hi-Lok, HL94 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL945 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-136-2915 |
| Schedule B: | 7318.19.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL94-5 Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.288 Inches Minimum And 0.292 Inches Maximum |
| Collar Overall Height: | 0.427 Inches Minimum And 0.447 Inches Maximum |
| Collar Inside Diameter: | 0.166 Inches Minimum And 0.170 Inches Maximum |
| Nominal Thread Size: | 0.164 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp 303se Overall |
| Material Document And Classification: | Qq-s-764 Fed Spec Single Material Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-riquet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_riquet+collars/HL94-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.