

# **P/N HL94-5**

## **Description**

Collar, tension application, oversized 303 stainless steel, cadmium plated, Hi-Lok, HL94 series collar

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL945

Minimum Qty (MOQ): 10

NSN: 5320-00-136-2915

Schedule B: 7318.19.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# **P/N HL94-5 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Collar Inside Diameter:	0.166 Inches Minimum And 0.170 Inches Maximum
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall
Thread Series Designator:	Unjc

# **How to Order**

Order this pin-rivet collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/HL94-5">https://military-fasteners.com/collars/pin\_rivet+collars/HL94-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.