

**Description**

tension application, oversized 303 stainless steel, cadmium plated, Hi-Lok, HL94 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL946
Minimum Qty (MOQ):	10
NSN:	5320-00-136-2913
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N HL94-6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.318 Inches Minimum And 0.322 Inches Maximum
<b>Collar Overall Height:</b>	0.437 Inches Minimum And 0.457 Inches Maximum
<b>Collar Inside Diameter:</b>	0.208 Inches Minimum And 0.212 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Qq-s-764 Fed Spec Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rievet+collars/HL94-6](https://military-fasteners.com/collars/pin_rievet+collars/HL94-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.