

# P/N HL94-6

Military-Fasteners.com

#### Description

tension application, oversized 303 stainless steel, cadmium plated, Hi-Lok, HL94 series collar

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	HL946
Minimum Qty (MOQ):	10
NSN:	5320-00-136-2913
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL94-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.318 Inches Minimum And 0.322 Inches Maximum
Collar Overall Height:	0.437 Inches Minimum And 0.457 Inches Maximum
Collar Inside Diameter:	0.208 Inches Minimum And 0.212 Inches Maximum
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall
Thread Series Designator:	Unjf

### How to Order

Order this pin-rivet collar from our inventory online by visiting <u>https://military-fasteners.com/collars/pin\_rivet+collars/HL94-6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.