

**Description**

Shear application, high temperature alloy, silver plated, Hi-Lok, HL97 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL975
Minimum Qty (MOQ):	2
NSN:	5320-01-005-4086
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL97-5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.283 Inches Minimum And 0.287 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.166 Inches Minimum And 0.173 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Iron Alloy 660 Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL97-5](https://military-fasteners.com/collars/pin_rivet+collars/HL97-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.